



EVO Stainless Steel Patisserie Counters

EVO60 / EVO90 / EVO120 / EVO150

2 Years Parts & Labour Warranty

2-3 Working Days Delivery

UK Service Support

Manufactured In Europe



This elegant Sterling Pro Green patisserie counter range (in Stainless Steel) is ideal for commercial environments such as cafés, conveniences stores and restaurants. Manufactured in Europe, this range features rear sliding doors for easy access, hinged front tempered glass for easy cleaning, LED lighting for each shelf, x3 refrigerated shelves, ventilated cooling and an efficient refrigeration system that is enhanced by the superb air-flow around each of the product shelves.

Model	Deck Area	Temperature Range	Max Ambient	Refrigerant	Dimensions (mm)		
EVO60-SS-R290A	0.94m ²	+3°C to +5°C	+25°C	R290a	W600	D785	H1400
EVO90-SS-R290A	1.41m ²	+3°C to +5°C	+25°C	R290a	W900	D785	H1400
EVO120-SS-R290A	1.88m ²	+3°C to +5°C	+25°C	R290a	W1200	D785	H1400
EVO150-SS-R290A	2.34m ²	+3°C to +5°C	+25°C	R290a	W1500	D785	H1400



EVO Stainless Steel Patisserie Counters

EVO60 / EVO90 / EVO120 / EVO150



Range Specifications

	EVO60-SS-R290A	EVO90-SS-R290A	EVO120-SS-R290A	EVO150-SS-R290A
GTIN Code	5060750320785	5060750320792	5060750320808	5060750320815
Dimensions (mm)	W600 x D785 x H1400	W900 x D785 x H1400	W1200 x D785 x H1400	W1500 x D785 x H1400
Deck Area	0.94m ²	1.41m ²	1.88m ²	2.34m ²
Shelving Included	3	3	3	3
Front Opening	Yes (For cleaning only)	Yes (For cleaning only)	Yes (For cleaning only)	Yes (For cleaning only)
Glass Type	Tempered	Tempered	Tempered	Tempered
Under-storage	No	No	No	No
Rear Sliding Doors	Yes	Yes	Yes	Yes
Exterior Finish	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Temperature Range	+3°C to +5°C	+3°C to +5°C	+3°C to +5°C	+3°C to +5°C
Max Ambient	+25°C	+25°C	+25°C	+25°C
Refrigerant	R290a	R290a	R290a	R290a
Energy Rating	N/A	N/A	N/A	N/A
Climate Class	3	3	3	3
Energy Consumption	N/A	N/A	N/A	N/A
Power Supply	13 amp plug	13 amp plug	13 amp plug	13 amp plug
Voltage	230/1N 50HZ	230/1N 50HZ	230/1N 50HZ	230/1N 50HZ
Cooling System	Fan assisted	Fan assisted	Fan assisted	Fan assisted
Defrost Type	Electrical	Electrical	Electrical	Electrical
Upper Lighting	Yes	Yes	Yes	Yes
Shelf Lighting	LED	LED	LED	LED
Digital Display	Yes	Yes	Yes	Yes
Lockable	No	No	No	No
Castors	No	No	No	No
Frost Free	No	No	No	No