



SALINA Serveovers
SALINA80/100 / 150 / 200 / 250 / 300



Specifications

Model	Glass Style	Deck Area	Storage Doors	Temperature	Max Ambient	Dimensions (mm) Width / Depth / Height			Refrigerant
SALINA80/100VCC	Curved	0.60m ²	1	+3°C to +5°C	+25°C	1040	900	1292	R452a
SALINA80/150VCC	Curved	0.83m ²	2	+3°C to +5°C	+25°C	1520	900	1292	R452a
SALINA80/200VCC	Curved	1.10m ²	2	+3°C to +5°C	+25°C	2000	900	1292	R452a
SALINA80/250VCC	Curved	1.38m ²	3	+3°C to +5°C	+25°C	2480	900	1292	R452a
SALINA80/300VCC	Curved	1.66m ²	3	+3°C to +5°C	+25°C	2960	900	1292	R452a
SALINA80/100VD	Flat	0.60m ²	1	+3°C to +5°C	+25°C	1040	900	1262	R452a
SALINA80/150VD	Flat	0.83m ²	2	+3°C to +5°C	+25°C	1520	900	1262	R452a
SALINA80/200VD	Flat	1.10m ²	2	+3°C to +5°C	+25°C	2000	900	1262	R452a
SALINA80/250VD	Flat	1.38m ²	3	+3°C to +5°C	+25°C	2480	900	1262	R452a
SALINA80/300VD	Flat	1.66m ²	3	+3°C to +5°C	+25°C	2960	900	1262	R452a

Features

13 amp plug	Electronic timed defrosting
Independent refrigerated under-storage	Neon lighting
Ambient internal display shelf	Slimline - only 900mm deep
Choice of flat or curved glass	Low energy consumption