



3, 5, 8 & 10 Grid Blast Chillers

SP0315BC / SP0523BC / SP0840BC / SP1050BC



2 Years Parts & Labour Warranty



2-3 Working Days Delivery



UK Service Support



The Sterling Pro Green 3, 5, 8 and 10 grid blast chiller range is constructed in Stainless Steel and is designed with a handful of features to reduce temperature loss and ensure protection of the environment. With 60mm thick (CFC-free) polyurethane insulation, this range also features height adjustable Stainless Steel legs, hinged doors with automatic return, sealed condenser units with ventilated condensers and ventilated grills on front panels.

Model	Grids	Chill Capacity	Freeze Capacity	Chilling Cycle (90°C to 3°C)	Freezing Cycle (90°C to -18°C)	Refrigerant	Dimensions (mm)		
SP0315BC	3	15kg	6kg	90 minutes	240 minutes	R452a	W570	D700	H514
SP0523BC	5	23kg	13kg	90 minutes	240 minutes	R452a	W790	D700	H850
SP0840BC	8	40kg	24kg	90 minutes	240 minutes	R452a	W790	D800	H1290
SP1050BC	10	50kg	30kg	90 minutes	240 minutes	R452a	W790	D800	H1420





3, 5, 8 & 10 Grid Blast Chillers

SP0315BC / SP0523BC / SP0840BC / SP1050BC

Range Specifications

	SP0315BC	SP0523BC	SP0840BC	SP1050BC
GTIN Code	5060750321522	5060750321539	5060750321553	5060750321546
Exterior Dimensions	W570 x D700 x H514	W790 x D700 x H850	W790 x D800 x H1290	W790 x D800 x H1420
Packaged Dimensions	W670 x D860 x H720	W895 x D810 x H1065	W895 x D910 x H1505	W895 x D910 x H1640
Grids	3	5	8	10
Chill Capacity	15kg	23kg	40kg	50kg
Freeze Capacity	6kg	13kg	24kg	30kg
Chilling Cycle	90 minutes	90 minutes	90 minutes	90 minutes
Freezing Cycle	240 minutes	240 minutes	240 minutes	240 minutes
Shelf Runner Gap	65mm	65mm	65mm	65mm
Shelving	N/A	GN1/1 or 600x400	GN1/1 or 600x400	GN1/1 or 600x400
Exterior Finish	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Interior Finish	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Max Ambient	N/A	N/A	N/A	N/A
Refrigerant	R452a	R452a	R452a	R452a
Insulation Thickness	60mm	60mm	60mm	60mm
Insulation Type	Polyurethane	Polyurethane	Polyurethane	Polyurethane
Gross Weight	62kg	98kg	145kg	160kg
Energy Rating	N/A	N/A	N/A	N/A
Climate Class	N/A	N/A	N/A	N/A
Power Supply	13 amp plug	13 amp plug	13 amp plug	13 amp plug
Voltage	230V/50HZ	230V/50HZ	230V/50HZ	230V/50HZ
Cooling System	Ventilated	Ventilated	Ventilated	Ventilated
Defrost Type	Automatic	Automatic	Automatic	Automatic
Self Closing Doors	Yes	Yes	Yes	Yes
Reversible Doors	No	No	No	No
Lighting	No	No	No	No
Lockable	No	No	No	No
Castors	No	No	No	No